

ROSA BUS

FUSO

ROSA SWB DELUXE

MANUAL or DUONIC AMT



THE SAFEST LIGHT DUTY BUS IN THE MARKET WITH AEB, LDWS, ESP, ABS, DRIVER AND FRONT PASSENGER SRS AIRBAG'S, LED HEADLAMPS AND REVERSE CAMERA AS STANDARD.

People Inc. Driver

22

Length

7.0M

Power/Torque

129kW / 430Nm

- Light rigid licence required
- Actual vehicle may differ from above image

FUSO

ROSA SPECIFICATIONS

MODEL

A	Deluxe SWB 22 Seat Manual (BE741GRMDFAA)
B	Deluxe SWB 22 Seat Duonic AMT BE741GRMDFAB


LENGTH

7.0M
7.0M

CONFIGURATION

High Back Fabric Seats with Lap/Sash Seat Belt
High Back Fabric Seats with Lap/Sash Seat Belt

Engine	
Engine Version	FUSO 4P10-T6 Diesel
Configuration	4 Cyl. In-line DOHC, 4-Valve
Type	Variable Geometry Turbo Charged Air to Air Intercooled
Displacement	3 litre (2998cc)
Bore	95.8mm
Stroke	104mm
Power (DIN)	129kW @ 2860~3500 rpm
Torque (DIN)	430Nm @ 1600~2860 rpm
Maximum Engine Speed	4100 rpm
Compression Ratio	17.5:1
Cooling System / Oil Cooler	Water cooled, 14.1L capacity/ Plate type engine oil cooler
Air Cleaner	Paper Element Type with Restrictor Indicator. Mounted Underbody (RH)
Emission Control	Diesel Particulate Filter (DPF) Exhaust Dash Display DPF Status 0~9 (Empty~Full) Parked Regeneration possible from 7~9 Selective Catalytic Reduction (SCR) after-treatment system (BlueTec)
Emission Level	ADR 80/03 - Euro VI



Fuel	
Injection System	Bosch Common Rail Electronic Direct Injection
Tank Type	Rectangular Steel Tank with Locking Cap
Fuel Capacity *	100 Litres
Filtration	Main Filter with Water Separator Function
AdBlue Exhaust Fluid Capacity	12 Litres
Speed Limiter	Speed Limited 100km/h
Notes	*Max Fill to approx 95% of Air Capacity

Cooling	
Fan Drive	Thermo modulated continuous control (Viscous)
Radiator	Corrugated Fin with Expansion Tank

Electrical	
Voltage	12V / 24V with Battery Equalizer
Battery Capacity	2x12V, 70Ah/5hr with Battery Equalizer
Battery Specification	115D31L x2
Headlamp Type	LED
Taillamp Type	LED - as of March 2021 production
Fog Light	LED

Clutch		
Clutch Model	A FUSO C4W30	B Fully Automated Dual Clutch (no clutch pedal)
Type	A Single Plate	B Dual Clutch (Wet Multi-plate)
Operation/Specification	A Hydraulic Control with Pedal Power Booster	B Automated Manual (no clutch pedal)

Transmission		
Version	A FUSO M038S5	B FUSO Duonic M038S6
Type/Speeds	A 5 Speed with In-Dash Gearshift Lever	B 6 Speed Automated Manual with Auto and Manual Modes
Features	A Synchronesh 1st - 5th and Rev	B Synchronesh 1st - 6th and Rev Virtually Instant Gear Changes In-Dash Gear Lever with Park Brake Position
Ratios	A 1st: 5.494 2nd: 3.038 3rd: 1.592 4th: 1.000 5th: 0.723 Rev. 5.494	B 1st: 5.397 2nd: 3.788 3rd: 2.310 4th: 1.474 5th: 1.000 6th: 0.701 Rev. 5.397
Park Interlock	Ignition Key (On) & Foot Brake Activated	

Front Suspension	
Type	Independent Double Wishbone with Coil springs, Transverse Leaf Spring and Double Acting Shock Absorbers

Rear Axle	
Type	Full Floating Hypoid
Axle Version	FUSO R033B
Capacity*	3800kg
Ratio	5.285:1
Notes	*See MAX LOADING for vehicle capacity.

Rear Suspension	
Type	Steel Suspension
Details	Long Taper with Stabiliser Bar and Shock Absorbers

Max Loading	
Front	2500kg
Rear	3800kg
Total	5900kg

Options	
Options	R72: Vinyl Seat Covering

Steering	
Type	Rack & Pinion with Integral Power Assistance
Steering Column	Tilt/Telescopic Adjustable

ROSA SPECIFICATIONS

MODEL

A	Deluxe SWB 22 Seat Manual (BE741GRMDFAA)
B	Deluxe SWB 22 Seat Duonic AMT BE741GRMDFAB

LENGTH

7.0M
7.0M

CONFIGURATION

High Back Fabric Seats with Lap/Sash Seat Belt
High Back Fabric Seats with Lap/Sash Seat Belt

Brakes

Type	Hydraulic Dual Circuit with Front and Rear Twin Calliper Disc Brakes
Size Front	235x40mm
Size Rear	235x40mm
Features	ABS plus EBD (Electronic Brake Distribution) Active Emergency Braking System (AEBS) Electronic Stability Program (ESP) Exhaust Brake Brake Priority System
Park Brake	Transmission
Auxiliary	Exhaust Brake

Wheels & Tyres

Wheel Type	Alloy Disc 16x5.5J
Wheel Size	16.0x5.5G-115
Tyre Size All	Michelin Tyres XJE4 Mix Energy 205/85R16LT 117/115L
Spare Tyre Carrier	Provided

Chassis

Type	Parallel Tapered Channel with Cross Members
------	---

Instruments

Gauges	Speedometer with LCD Odometer & Dual Tripmeter Tachometer (Yellow Zone indicates safe exhaust operating zone) Fuel Level Water Temperature
Warning Lamps	AEBS LDWS ESP ESP Off Turn Signal Headlamps High Beam Hill Holder Auxiliary Brake Parking Brake Oil Pressure Battery Charging Vacuum Pressure DPF Regeneration DPF Fill Level Adblue Fill Level Passenger door open Rear Emergency Door Open Fog Lamp

Multi-Media Package

Satellite Navigation	Maps with heavy vehicle weight, length, height & hazardous material selectable restrictions with 3 years of Map updates
Colour Display	7 inch LCD with touch screen control
Phone Connectivity	Bluetooth® hands free
Audio Visual Entertainment	Bluetooth® music streaming compatible Digital radio DAB+ (also AM/FM for areas not covered by DAB+) USB & 3.5mm/AUX port
Reversing Camera	1 Reverse Camera fitted as standard
Compatible	Display can accept up to 4 additional cameras#
Optional Accessories (available at additional cost)	Rear Mounted Parking Sensor Kit High or Low Tyre Pressure Monitoring System
Notes	# Cameras available through spare parts

Exterior

Windscreen	Laminated Tinted with Darker Upper Band
Side Windows	Fixed Type with Dark Tint
Body Colour	Rising White with Colour Code Bumpers Black Side Window Sash
Towing Hook	Front

Interior

Lighting	Access Step Light & LED Interior Lights
Floor	Heavy Duty Vinyl Floor Covering

Active Safety

Safety Systems	AEBS - Advanced Emergency Braking System LDWS - Lane Departure Warning System ESP - Electronic Stability Program ABS - Anti-lock Braking System ASR - Anti Slip Regulator LED Headlamps
Reverse Warning	Buzzer
Passenger Access Door	Accelerator Interlock & Pre-Warning Buzzer

Passive Safety

Airbags	SRS Airbag - Driver and Front Passenger
Body Strength	Fully ADR 59 & 68 Roll Strength Compliant
Emergency Exits	4 Exits (1 LH & 2 RH Windows with Emergency Hammers and Rear Emergency Door)
Emergency Operational Decals	Internal & External
Rear Swing Door - Opening Direction	Outward
Rear Door Locking	Automatic when Ignition Key in Off Position
Seat Belts - Driver & Driver Assistant	3 Point ERL Lap Sash
Fire Extinguisher	Provided

Driver Comfort & Features

Driver's Seat	Low Back Sliding with Head Rest Adjustable Height & Back Angle
Visibility Mirrors	LH & RH External Rear View Additional Front Left Clearance Internal Rear Vision Rear Mounted Reversing
General	Power Driver's Window. Cup Holder. Sun Visors Driver and Front Passenger. Central Locking. 12V Accessory Power Outlet.

Air Conditioning (Separate Unit)

Control	Full Auto
Capacity	11.6 kW JIS
Distribution	Integrated Roof Ducts located throughout Cab
Intake	Switchable Fresh Air Duct on Roof at Rear of Cab

Cabin Heating / Demisting

Heaters	Forward Cabin plus Passenger Units throughout Cab
Demisters	Forward and Rear Cabin

ROSA SPECIFICATIONS

MODEL	LENGTH	CONFIGURATION
A Deluxe SWB 22 Seat Manual (BE741GRMDFAA)	7.0M	High Back Fabric Seats with Lap/Sash Seat Belt
B Deluxe SWB 22 Seat Duonic AMT BE741GRMDFAB	7.0M	High Back Fabric Seats with Lap/Sash Seat Belt

Passenger Access & Seating

Passenger Door	Swing Type Electric Automatic with Step Illumination light & Dash Interlock Warning
Passenger Seats	Fixed High Back
Seat Belts	ERL 3 Point Lap Sash (ADR68/00)
Child Restraint	6x Anchor points
Trim	Fabric
Internal Lights	Located overhead and on steps
Interior	Fully trimmed including Side Windows, Rear Pillars & Emergency Door surrounds
External Trim	Black Exterior Front & RH Door Panel Inserts
Other	O/Head Storage above Windscreen with Centrally Mounted Clock
Modesty Panel - Front Passenger Seat	Front Passenger Seat

Service Intervals

Interval*	15,000km or 6 Months (Whichever occurs first)
Notes	* based on normal operating conditions and may be reduced when operating under severe conditions.

Warranty

Basic/Powertrain	5 Years or 200,000kms (whichever occurs first)
Cab Perforation/Anti Corrosion	5 Years

ATM (towing capacity)

Without Trailer Brakes	715kg
With Trailer Brakes	1615kg

Performance


Turning Circle (kerb to kerb)	12.6m
-------------------------------	-------

Mass (estimated)*

Total*	A 3980kg	B 4050kg
Note:	* Mass est. includes oil, fuel, water, spare tyre carrier bracket, spare tyre and standard tool set. Weights provided are subject to 3.5% variation +/-	

Dimensions (mm)

Width Overall (excluding mirrors)	2070
Width Front Track	1665
Width Rear Track	1505
A - Length Overall (B+C+D)	6990
B - Length Front Overhang	940
C - Length Wheelbase	3995
D - Length Rear Overhang	2055
F - Height Overall	2755
G - Height Floor to Headliner	1860
H - Height Access Door	1715
I - Height Emergency Exit	1480
J - Height First Access Door Step to Ground	380
K - Height Second Access Door Step to Floor	295
L - Width Door Access	600
N - Width Single	465
O - Width Driver's Seat	500
P - Height Passenger Aisle	465



Call 1800 033 557

or visit fuso.com.au

Unless specified in writing herein the accessories, applications, bodies or equipment depicted in this are for illustration purposes only and may not be available from Daimler Truck Australia Pacific Pty Ltd. ABN 86 618 413 282 DTAuP. No representation or warranty whatsoever is given in relation to any accessories, applications, bodies or equipment or suitability of same that are shown herein that may be manufactured, supplied or fitted by a party other than DTAuP. DTAuP reserves the right without notice or obligation to discontinue or make changes to the colour, designs, materials and specifications of the products and options referred to herein at any time. For the most current information and in order to ascertain which accessories, applications, bodies and equipment are available from DTAuP please contact your authorised FUSO dealer. Fuso is a registered trademark of Daimler Truck Australia Pacific Pty Ltd. Copyright DTAuP. Reproduction in whole or part prohibited without written approval. Part Number TSR71A. Valid from 17-May-21.